



Search: Support

- [Solutions](#)
- [Services](#)
- [Products](#)
- [Learning Center](#)
- [Support](#)
- [About us](#)
- [How to buy](#)
- [Government](#)

- [Drivers](#)
- [Firmware Updates](#)
- [Documentation](#)
- [Diagnostics, Utilities and MIBs](#)
- [Cabling](#)
- [Knowledge base](#)
- [Warranty registration](#)
- [Support forum](#)
- [Service agreements](#)
- [Return merchandise](#)
- [Online support request](#)
- [Manage Subscriptions](#)

[Home](#) > [Support](#) > [Knowledge Base](#) > [Result](#)

[Printable view](#)

## Temperature Ratings

Following are the temperature ratings of some Digi products and accessories:

Description	Product	Operating Temp	Storage Temp
(2.1dBi) Articulating, RPSMA antenna	A09-HASM-675	-20C to +65C	
(2.1 dBi) Non-articulating, RPSMA antenna	A09-HSM-7	-20C to +65C	
RF cable, LMR-195, RPSMA male to N-male cable	JR2N1-CL1-xx	-40C to +85C	
Power supply, 9VDC 400mA 2.1mm/5mm barrel jack.	JP4P2-9V4-6F	0C to +40C	-20C to +65C
Power Supply, 9V 1.1A	JP5P2-9V11-6F	0C to +40C	-20C to +65C
Please contact Digi Technical Services for temperature ratings on other products.			

